

## Battery powered Digital Pressure gauge

### Model: MDG10

#### Applications

- Measure gas liquid oil and other corrosive medium
- Test bench / gauge repair facilities
- Hydraulics and pneumatics
- Test measurement and validation
- Process industry: Chemical/petro chemical, power stations, food and beverage, offshore oil rigs, pulp and paper, environmental technology, machine building and general plant construction

#### Special features

- Measuring ranges from -100 ... 100kpa 0... 1600 bar
- Accuracy 0.4 %, 0.2 option
- Temperature indicator -20 ... 70 °C
- Zero clearing, backlight ON/OFF
- View Max/Min working mode
- Multi selectable pressure units
- Excellent shock and vibration resistance
- Option: Rotatable instrument head, backlighting
- Option: Intrinsically safe
- Bar graph indicator
- Scale ranges up to 0 ... 1,600 bar
- Temperature compensation: 0 - 60 °C

#### Description

##### Robust, precise digital indicator

The robust stainless steel case and the battery power enable a flexible operation in various applications and industries. For a precise and quick on-site reading of a pressure value, a digital indicator is the ideal solution. The bar graph display and drag pointer function integrated into the display, as well as retrievable Min/Max peak values, enable effective analysis of the measuring point.

##### Customized installation

the model MDG 10 can be easily adapted to local conditions. The backlighting also provides easy readability of the display in poor lighting conditions.



## Description

- Accuracy 0.4% of full scale option 0.2% of full scale
- Sensor Thin film (<7 Mpa) or Ceramic strain gauge(0.6 Mpa to 7 MPa ranges)
- Case Material 304 St. steel
- Case Diameter 80 mm (3") nominal
- Connection Bottom
- Display 4-digit LCD
- Pressure Units M Pa , kPa, bar, m bar, psi, kgf/ cm2, mmHg, mH2o
- Measurement Res. 14 bit
- Sampling Time 3 Time second
- Process Connection 304 St. steel 1/2", 1/4", M20\*15 and other
- Pressure Ranges Positive, negative and compound
- Over Pressure 150% full scale
- Power Supply 3 V (two pieces AAA battery)
- Battery operating time Continuous working for 3600 hour
- Acquisition speed (1-10)/sec
- Medium Temperature -20...70°C
- Ambient Temperature -10...50°C
- Temp. Compensation 0...60°C
- Environ. Protection IP 54

code	bar	Range (kPa)	mBAR	mmHg	mmH2O	Mpa	Kgf/cm2		
M1	-1 ... 0	-100 ... 0	-1000 ... 0	-750.0671 ... 0	-10197.162 ... 0	-0.1 ... 0	-1.019 ... 0		
M2	-1 ... +1	-100 ... +100	-1000 ... 1000	-750.0671 ... +750.0671	-10197.162 ... +10197.162	-0.1 ~ +0.1	-1.019 ... +1.0197		
M3	-1 ... +2	-100 ... +200	-1000 ..2000	-750.0671 ... +1500.12	-10197.162 ... +20394.32	-0.1 ~ +0.2	-1.019 ... +2.039		
M5	-1 ... +5	-100 ... +500	-1000 ... 5000	-750.0671 ... +3750.380	-10197.162 ... +50985.81	-0.1 ~ +0.5	-1.019 ... +5.0985		
M7	-1 ... +10	-100 ... +1000	-1000 ... 10000	-750.0671 ... +7500.62	-10197.162 ... +101971.6	-0.1 ~ +1	-1.019 ... +10.1972		
M00	0 ... 0.25	0 ... 25	0 ... 250	0 ... +187.5154	0... +25492.90	0 ~ +0.025	0 ... +0.2549291		
M01	0 ... 0.4	0 ... 40	0 ... 400	0 ... +300.0247	0... +4078.86	0 ~ 0.04	0 ... +0.4078		
M02	0 ... 0.6	0 ... 60	0 ... 600	0 ... +450.037	0... +6118.29	0 ~ 0.06	0 ... +0.6118		
M03	0 ... 1	0 ... 100	0 ... 1000	0 ... +750.0617	0... +10197.16	0 ~ 0.1	0 ... +1.0197		
M04	0 ... 2.5	0 ... 250	0 ... 2500	0 ... +1875.15	0... +25492.90	0 ~ 0.25	0 ... +2.54929		
M05	0 ... 4	0 ... 400	0 ... 4000	0 ... +3000.247	0... +40788.64	0 ~ 0.4	0 ... +4.0788		
M06	0 ... 6	0 ... 600	0 ... 6000	0 ... +4500.37	0... +61182.97	0 ~ 0.6	0 ... +6.1182		
M07	0 ... 10	0 ... 1000	0 ... 10000	0 ... +7500.617		0 ... 1	0 ... +10.197		
M08	0 ... 16	0 ... 1600	0 ... 16000	0 ... +12001		0 ... 1.6	0 ... +16.3155		
M09	0 ... 25	0 ... 2500	0 ... 25000	0 ... +18751.5		0 ... 2.5	0 ... +25.4929		
M10	0 ... 40	0 ... 4000	0 ... 40000	0 ... +30002.47		0 ... 4	0 ... +40.788		
M11	0 ... 60	0 ... 6000	0 ... 60000	0 ... +45003.7		0 ... 6	0 ... +60.182		
M12	0 ... 100	0 ... 10000	0 ... 100000	0 ... +75006.17		0 ... 10	0 ... +101.97		
M13	0 ... 160	0 ... 16000	0 ... 160000	0 ... +120010		0 ... 16	0 ... +163.155		
M14	0 ... 250	0 ... 25000				0 ... 25	0 ... +254.92		
M15	0 ... 400	0 ... 40000				0 ... 40	0 ... +407.88		
M16	0 ... 600	0 ... 60000				0 ... 60	0 ... +611.82		
M17	0 ... 700	0 ... 70000				0 ... 70	0 ... +713.801		
M18	0 ... 1000					0 ... 100	0 ... +1019.7		
M19	-1 ... 40	-100 ... 4000	-1000 ... 40000	-750.0671 ... +30002	-10197.162 ... +40788	-0.1 ... 4	-1.019 ... +40.788		
L1	15 mbar	L2	25 mbar	L3	60 mbar	L4	100 mbar	L5	160 mbar

For special range, please use the code XX and mention the range in the order



**MDG 10 Battery powered Digital Pressure gauge**

ORDERING CODE	Example:	MDG 10	M10	3	T	2	N	S	AT	I	WA	Note
<b>Range</b>												
Select a range from the table			M10									
<b>Dial Size/Model Code</b>												
2 - 63 mm(2.12")												
3 - 80 mm(3")				3								
4 - 100 mm(4")												
<b>Process Connection Type</b>												
T- Bottom					T							
B - Back												
<b>Process Connection Sizes</b>												
2 - G ¼ Male Dial 63 G ½ Male NS100,160 Dial						2						
4 - ¼ NPT Dial 63 Male ½ NPT Male NS100,160 Dial												
6 - Customer												
<b>Case Cover</b>												
N - None							N					
C - With cover												
<b>Process Connection Material</b>												
S - 304 Stainless steel								S				
L - 316L Stainless steel												
H - Hastelloy												
C - Customer												
<b>Accuracy</b>												
AT - 0.4% (std.)									AT			
AC - 0.2%												
<b>Certificate</b>												
N - None												
I - Intrinsically safe ( Ex ib IIC T4)										I		
<b>Options</b>												
CM - Material Traceability certification												
CP - Hydrostatic testing with certificate												
CL - Cleaning for special service												
YW -316L Stainless steel case												
OS - Overload stop												
CC - Calibration certificate												
NH - Stainless steel tag wired to case												
AT - ATEX												
WA - One year warranty											WA	
Other												





Address: 7191 Yonge street, Toronto, Canada

Tel: +16472221281(5 line)

Web: [www.madecotech.com](http://www.madecotech.com)

Email: [Info@madecotech.com](mailto:Info@madecotech.com)