

Digital pressure transmitter controller Model MDI10

Description

MDI10 digital pressure controller combine pressure measuring, display, control & transmit together. Can be easily installed to measuring pressure at the scene. It can set the zero output, span output, pressure of contact point and control pressure with key at scene.

Application

- Machine tools
- Hydraulics and pneumatics
- Pumps and compressors
- Machine building

Special features


- 4 digit display the current pressure value
- Set on-off point of relay by pressure and delay switch output
- On-off point of relay can be setted arbitrarily between zero and span
- Button and adjust set the various parameters at the scene, easy to operate
- 2-way switching output, with carrying capacity of 1.2A
- Analog output 4~20mA



Specification


Measurement Range	-0.1 ... 0~100mbar ... 1000bar
Proof pressure	≤1.5X rated pressure
Pressure type	Gauge, absolute ,sealed gauge
Accuracy	± 0.25% (typical)±0.5% (Max.)
Long stability	±0.3%F.S/year
Temperature Error-Zero	±0.03%F.S ≤100KPa ±0.02%F.S (>100KPa)
Temperature Error- Span	±0.03%F.S ≤100KPa ±0.02%F.S (>100KPa)
Temperature Compensation	-10 ~80C
Operating Temperature Range	-30℃ ~80℃
Storage Temperature Range	-40℃ ~125℃
Power supply	24VDC 220VAC
Output signal	Analog output :4 ~20mA;Digital output :RS485
Pressure port	M20×1.5 G1/2 or customize
Relay control	1~ 4 way relay controlor electron switch value control
Life of contact point	More than 100000 times
Display	-1999~ 9999
Housing material	1Cr18Ni9Ti stainless steel
Diaphragm material	316L
Oring	Fluororubber
Cable	Polyethylene
Insulation resistance	100MΩ 100VDC
Protection	IP65

Dimension(Unit: mm)




Electric Connection

PIN	COLOR	DEFINITION
1	Brown	+V
2	White	A1 alarm
3	Blue	GND
4	Black	A2 alarm
5	Gray	Signal + OUT



Ordering example : MDI10 01-A-10-X-D1-S1-B6-J3-G



Ordering note

- Media must be compatible with wet part.
- When release order, please mark power supply, accuracy, number of control point and whether need Rs485 interface.
- To ensure the products can work reliably, we suggest that customer install lightning protection device and make sure products & power are earthed.
- Special requirement, such as strong shock, moment vibration, strong electromagnetism, radio frequency interference, please consult us.

Ordering information

MDI10	Intelligent pressure controller			
	Electrical Connection			
	A	Circular connector		
	B	Din connector		
	C	Direct outlet 1.5 meter		
		Range	-0.1...0 . . . 1000Bar	
		(0-X) Psi or Bar	X: actual range	
			Code	Power supply
			D1	24VDC
			D2	220VAC
			Code	Output signal
			S1	4~20mADC
			S2	1~5VDC
			S3	0~5VDC
			S4	0~10mADC
			Code	Output function
			B5	One-way relay
			B6	Two-way relay
			B7	Three-way relay
			B8	Four-way relay
			B9	Four-way relay RS485 interface
			B10	One-way relay switching value output
			B11	Two-way switch value
			Code	Pressure port
			J1	M20×1.5 Male
			J2	G1/2 Male
			J3	G1/4 Male
			J4	others
			Code	Pressure type
			G	Gauge pressure
			A	Absolute pressure
			S	Sealed gauge



Address: 7191 Yonge street, Toronto, Canada

Tel: +16472221281(5 line)

Web: www.madecotech.com

Email: Info@madecotech.com