

Pressure transmitter For sanitary applications Model MDS5

Applications

- For gases, compressed air, vapour, liquids, pastes and powdery media
- Ultra-pure steam systems for SIP
- Hydrostatic level measurement:
- Vacuum pressure monitoring, e.g. vacuum conveyors, pump monitoring
- Food and beverage manufacturing, pharmaceutical industry, biotechnology, sanitary applications

Special features

- Flush diaphragm with a surface roughness of $Ra < 0.38 \mu m$
- Fully welded
- Suitable for SIP and CIP
- Ingress protection up to IP 65

Description

The pressure transmitter MDS5 is designed especially for the requirements of the food and beverage, pharmaceutical and biotechnology industries.

It is particularly suitable for the special conditions of CIP/SIP cleaning processes, such as chemical stability towards cleaning liquids and high temperatures.

The flush diaphragm is directly welded to the process connection. This guarantees a service-free connection of the process connection and the measuring cell so that additional sealings are not required.

For dead-space free instrumentation, aseptic process connections (clamp, threaded) are available.

The MDS5 pressure transmitter is ideally suited to fulfil the stringent demands of sanitary applications



The measuring range covers 0 ... 250 mbar up to 0 ... 200 bar. The MDS5 pressure transmitter is powered with a DC voltage of 10 (14) ... 30 V. Available electronic output signals are 4 ... 20 mA, 0 ... 20 mA or 0 ... 10 V output.

A stainless steel case with an ingress protection of up to IP 65 offers a secure protection for external cleaning with splashed water and enables its use in high-humidity environments. Through the integrated cooling section, process temperatures of up to 60°C can be realised.

Specification

Measurement Range	0 ... ~250mbar~200 BAR
Proof pressure	≤1.5X rated pressure
Pressure type	Gauge, absolute ,sealed gauge
Accuracy	±0.5% (typical) ±0.25%(option)
Long stability	±0.1%F.S/year (typical) ±0.2%F.S/y ear (Max.)
Temperature Error- Zero	±0.03%F.S/°C (≤100KPa) ±0.02%F.S/ °C (>100KPa)
Temperature Error -Span	±0.03%F.S/°C (≤100KPa) ±0.02%F.S/ °C (>100KPa)
Operating Temperature Range	-10°C~60°C
Storage Temperature Range	-40°C~85°C
Power supply	9 ~36VDC、15VDC
Output signal	4~20mA 0.5 ~4.5VDC 1 ~ 5VDC 1 ~ 10VDC
Process connection	Tri-clamp 1 1/2" or 2"
Housing material	1Cr18Ni9Ti stainless steel
Diaphragm material	Fully welded 316L



Ordering Information

MD S 5X	Code	Dimension			
	5	Circular connector M12*1 4pin			
	6	Cable with 1.5 meter			
	7	Mini DIN			
	8	Big Din			
		Pressure range	0. . . 250mbar...200 BAR		
		(0-X)PSI or BAR	X: measurement range		
		Code	Power supply		
		D1	24VDC		
		D2	5VDC		
		D3	Others		
		Code	Output signal		
		S1	4~20mADC	S5	0~20mADC
		S2	1~5VDC	S6	0~10VDC
		S3	0~5VDC	S7	0.5~4.5VDC
		S4	0~10mADC		
		Code	Pressure port		
		J1	1 1/2"		
		J2	2"		
		J5	Others		
			Code	Pressure type	
			G	Gauge	
			A	Absolute pressure	
			S	Sealed pressure	

Ordering note:

1. Media must compatible with wetted part.
2. To ensure the products can working reliable, we suggest that customer install lightning protection device and make sure products & power are earthed.
3. Special requirement, such as strong shock, moment vibration, strong electromagnetism, radio frequency interference, please consult us.

Warranty:

Pressure transmitters have a limited one year warranty to the original purchaser. MADECO will replace or repair defective products free of charge. This warranty does not apply to any units have been modified, misused, neglected.



Address: 7191 Yonge street, Toronto, Canada

Tel: +16472221281(5 line)

Web: www.madecotech.com

Email: Info@madecotech.com